

• TRUSTED QUALITY SINCE 1921 •
RUST-OLEUM®
SPECIALTY

RUST-OLEUM® OUTDOOR FABRIC PAINT

DESCRIPTION AND USES

Rust-Oleum® Outdoor Fabric Paint is an easy way to refresh your worn outdoor fabrics with color. It provides broad coverage with excellent adhesion and flexibility. Fabrics stay soft* to the touch and maintain long-lasting color. Its UV and weather resistant barrier makes it ideal for outdoor fabrics. Great for use on outdoor furniture cushions, pillows and more.

PRODUCTS

SKU	DESCRIPTION (Aerosol)
-----	-----------------------

358831	Dark Red
358832	Navy
358834	Khaki
358839	Medium Gray
358842	Turquoise
379550	Graphite
379552	Marina Blue
379554	Chili Red
379555	Ink Blue

PRODUCT APPLICATION

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT

SURFACE PREPARATION

Ensure all debris is removed. Clean with soap and water, rinse and let dry.

PAINTING CONDITIONS

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist. Works best on weathered outdoor polyester fabrics. For other outdoor fabrics, additional coats may be required.

PRODUCT APPLICATION (cont.)

APPLICATION

Shake can vigorously for one minute after mixing ball begins to rattle. Shake often during use. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Hold can upright 6-8" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply a light coat. Wait 60 minutes between each additional coat. Too many coats or heavy application could result in a stiffer feeling fabric and blotching.

DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 1 hour and to handle in 2 hours. Fully dry in 24 hours. Machine washable in 3 days.

CLEAN-UP

When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean up wet paint with soap and water. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse it with warm water and wipe off. Do not insert any object into can valve opening.

*Softer than regular spray paint.

	TECHNICAL DATA	SPC-110
• TRUSTED QUALITY SINCE 1921 • RUST-OLEUM® SPECIALTY	RUST-OLEUM® OUTDOOR FABRIC PAINT	

PHYSICAL PROPERTIES

		OUTDOOR FABRIC PAINT
Resin Type		Polyurethane
Pigment Type		Varies with color
Solvents		Water, Ethanol
MIR		0.3-05 Max
Fill Weight		12 ounces
Practical Coverage (assumes 15% material loss)		Approximately 5.5 sq. ft./can
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	1 hour
	Handle	2 hours
	Recoat	60 minutes
	Full Cure	24 hours
Shelf Life		24 months
Flash Point		100°F
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 877-385-8155
www.rustoleum.com/specialty

Form: ARJ-1938
Rev.: 100323