



# MOLD BLOCKING PRIMER

Paint directly over existing mold, mildew, odor causing bacteria, and other fungal organisms

Top coat in 30 minutes

Excellent hide

Great for small projects & touch-ups

Blocks Stains & Odors



Before

After

Interior/Exterior • White

ACTIVE INGREDIENT  
3-Iodo-2-Propynyl Butyl Carbamate:.....0.15%  
Other Ingredients:\*.....99.85%  
TOTAL:.....100.00%

NET WT.  
13 OZ.  
(368 g)

KEEP OUT OF REACH OF CHILDREN  
CAUTION: See First Aid statement on back panel.

EPA Reg. No. 69587-6  
EPA Est. No. 69587-MD-001

\*Contains petroleum distillates, xylene or xylene range aromatic solvents

Manufactured by Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, IL 60061

**Mold Blocking Primer** is an EPA-registered protective coating that can be used to paint over\* all existing mold, mildew, fungi, and odor causing bacteria and any other fungal organisms. Mold Blocking Primer is formulated for use on non-porous interior and exterior applications and may be applied in factories, warehouses, storage facilities, refrigerated storage facilities, office buildings, residential living, schools, hospitals, veterinary care facilities, elderly care facilities, prisons and correction facilities, wash houses, restaurants, fitness centers and locker rooms, attics, basements, window frames, bathrooms, wall cavities, baseboards, sub-floors and tabletops. Mold Blocking Primer can be used with any topcoat.

### DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Check with all local, state and federal regulations prior to using or working with this product. Fix the source of any moisture problems prior to remediation. Do not attempt to salvage damaged or structurally unsound building materials. Consult a qualified professional to perform a thorough inspection and supply work specifications appropriate to the project.  
**SURFACE PREPARATION:** \*For applications that have existing wet, slimy, heavy soiled, gross filth, overgrowth, or loose material on the substrate a pre-cleaning step is required. Physically or mechanically remove gross filth, heavy soil, overgrowth or loose material including dirt, grease and oily films before application and ensure the substrate is free of slime or excessive moisture to ensure long-term adhesion and product performance particularly on exterior surfaces. If mold or mildew needs to be removed prior to application, remove with a mildew remover that is EPA registered and let dry. Wear eye, skin, and NIOSH approved respiratory protection. Patch surface irregularities with appropriate patching compounds.

**ATTENTION!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**APPLICATION:** Mold Blocking Primer is a ready to use product. Use at room temperature (70°F) in a well ventilated area - do not use in high humidity conditions. Shake can vigorously until ball inside can rattle. Turn upside down and continue shaking for one minute - shaking occasionally during use. If ball does not rattle, do not strike can. Contact Rust-Oleum. Spray 10-12" from object with short dusting strokes. If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick pin or other object into the stem.

**Mold, Mildew, Fungi, and Odor Causing Bacteria Control:** Mold Blocking Primer will reduce the growth of all mold, mildew and fungal organisms for up to 7 days. Apply Mold Blocking Primer generously and uniformly, ensuring that the surface is completely coated. Allow to dry.

**COVERAGE:** Approximately 20 sq. ft. per can

**DRY TIME:** Dries in minutes; topcoat in 30 minutes with latex or oil-base paints. For optimal protection, apply a topcoat that prevents mold & mildew on the paint film within 72 hours of application. Full adhesion and hardness develops in 7 days. For best results allow primer to cure overnight when applying strong solvent-base topcoats.

**CLEAN UP:** Wipe off tip before storing. Clean up wet paint with xylol or mineral spirits.

### STORAGE & DISPOSAL:

Do not contaminate water, food or feed by storage or disposal.

**STORAGE:** Store between 32-86° (0-30C) in a secure area inaccessible to children and away from food or feed.  
**Pesticide Disposal and Container Handling:** Nonrefillable container. Do not reuse or refill this container. Do Not Puncture or Incinerate! If empty, Place in trash or offer for recycling, if available. If partly filled: Call your local solid waste agency for disposal instructions.

### PRECAUTION STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**CAUTION:** Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Avoid contact with skin or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Wear gloves.

### FIRST AID

- |                      |                                                                                                                                                                                                                                                                                                              |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>IF ON SKIN:</b>   | <ul style="list-style-type: none"> <li>Take off contaminated clothing</li> <li>Rinse skin immediately with plenty of water for 15-20 minutes</li> <li>Call a poison control center or doctor for treatment advice</li> </ul>                                                                                 |
| <b>IF SWALLOWED:</b> | <ul style="list-style-type: none"> <li>Immediately call a poison control center or doctor</li> <li>Do not induce vomiting unless told to do so by a poison control center or doctor</li> <li>Do not give any liquid to the person</li> <li>Do not give anything by mouth to an unconscious person</li> </ul> |

**Note to Physician:** Contains petroleum distillate. Vomiting may cause aspiration pneumonia.

For 24 hour emergency information on this product, call the National Pesticides Information Center: 1-800-858-7378 (6:30AM to 4:30PM Pacific Time), seven days a week. During other times call the Poison Center: 1-800-222-1222. In case of emergency call 847-367-7700. Have the product container/label with you when calling Poison Control Center, doctor, or going for treatment.

### ENVIRONMENTAL HAZARDS

This product is toxic to fish. To protect the environment, do not allow pesticide to enter or run off into storm drains, drainage ditches, gutters or surface waters. Applying this product in calm weather when rain is not predicted for the next 24 hours will help ensure that wind or rain does not blow or wash pesticide off the treatment area.

### PHYSICAL OR CHEMICAL HAZARDS

Extremely flammable. Contents under pressure. Keep away from fire, sparks, and heated surfaces. Do not puncture or incinerate container. Exposure to temperatures above 130°F may cause bursting.

**SATISFACTION GUARANTEED:** If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-888-855-1774 for product replacement or a full refund of the purchase price. Refer to product number and batch code at bottom of can.

Primer - MIR less than 0.70g O<sub>2</sub>/g of product; VOC less than 60% by weight.



11 Hawthorn Pkwy., Vernon Hills, IL 60061  
888-855-1774 [rustoleum.com/zinsser](http://rustoleum.com/zinsser)

Made in USA | Hecho en E.U.A.

©2019 Rust-Oleum Corporation 351966 0619

Product No. 287512



0 20066 295 18 9