

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

HEAVY-DUTY DEGREASER



**CLEANS TOUGH
GREASE &
OIL STAINS**

*Concentrated Formula
Promotes Adhesion of
Paints, Stains & Sealers*

*Use on Garages, Basements,
Driveways, Sidewalks,
Patios & More!*

*Environmentally Friendly;
Won't Hurt Grass or Plants*

32 FL. OZ. (1 QT.) 946 mL

**#1 TRUSTED
BRAND FOR
PROTECTION**



WARNING: IRRITANT.
SEE OTHER CAUTIONS ON BACK PANEL.

¡ADVERTENCIA! IRRITANTE.
VEA OTRAS PRECAUCIONES EN PANEL TRASERO.

For Use with ALL Concrete Coatings Including

EPOXYSHIELD®

ROCKSOLID®

RUST-OLEUM® HEAVY-DUTY DEGREASER is specially formulated to clean grease and oil stains from concrete surfaces and is recommended for use prior to painting, staining, and sealing. Use at full strength to clean tough grease & oil stains, transmission & brake fluids, gasoline, anti-freeze and other stains from concrete surfaces. For general purpose cleaning, add 1 quart (32 oz.) of degreaser to 1 gallon (128 oz.) of water and mix thoroughly before cleaning. To keep your painted floor looking great, wash with 1 cup (8 oz.) of degreaser added to 1 gallon (128 oz.) of water.

WHERE TO USE:

Garages • Basements • Driveways • Sidewalks • Porches • Patios • Stairs

PREPARATION:

Wear protective clothing and eyewear when applying product. Wipe up excess oil and grease spills. Scrape and sweep away dirt and loose contaminants on surface.

MIXING INSTRUCTIONS:

Use **RUST-OLEUM® HEAVY-DUTY DEGREASER** at full strength to clean tough stains. Dilute 1:4 [1 qt. (32 oz.) degreaser in 1 gal. (128 oz.) water] for general purpose cleaning. To keep your painted floor looking great, dilute 1:16 [1 cup (8 oz.) degreaser in 1 gal. (128 oz.) water]. Stir diluted solution thoroughly. Avoid splashing.

DILUTION TABLE

	Tough Stains	Full strength
General Purpose Cleaning	1 qt. (32 oz.) degreaser in 1 gal. (128 oz.) of water	
Painted Surfaces	1 cup (8 oz.) degreaser in 1 gal. (128 oz.) of water	

APPLICATION INSTRUCTIONS:

Wear protective clothing and eyewear when applying product. Wipe up excess oil and grease spills. Scrape and sweep away dirt and loose contaminants on surface. Wet the surface first by spraying with a garden hose. Then apply the product (full strength for tough stains, diluted for general purpose cleaning and painted floors) and thoroughly scrub surface with a stiff bristle brush or broom. Wait 10-15 minutes while **RUST-OLEUM® HEAVY-DUTY DEGREASER** lifts stains from surface. Wipe up excess degreaser with rags or paper towels to keep contaminants from spreading. Rinse thoroughly with fresh water. Repeat applications may be necessary for difficult stains. Remove excess water with a squeegee or mop.

STORAGE & DISPOSAL:

Store at room temperature. Keep container closed when not in use. Dispose of container and/or unused contents in accordance with local, state and federal regulations.

PROTECT FROM FREEZING

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS SODIUM METASILICATE. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. **USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air and use a properly fitted respirator (NIOSH approved for organic vapor with P series particulate prefilter) will offer additional protection; however, obtain professional advice before using a respirator. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN—DO NOT TAKE INTERNALLY.**

¡ADVERTENCIA! ¡IRRITANTE! DAÑINO SI ES TRAGADO. CONTIENE HIDRÓXIDO DE SODIO. PUEDE CAUSAR IRRITACION DE OJOS, NARIZ Y GARGANTA. EVITE EL CONTACTO CON LA PIEL Y OJOS Y EVITE RESPIRAR LOS VAPORES Y EL ROCÍO. UTILICE PROTECCIÓN PARA LOS OJOS Y ROPA PROTECTORA. **USAR ÚNICAMENTE CON VENTILACIÓN ADECUADA.** Para evitar respirar los vapores y el rocío, abra ventanas y puertas o use otras medidas para asegurar la entrada de aire fresco durante la aplicación y secado. Si siente lagrimeo, dolor de cabeza o mareo, incremente el aire fresco. Si se usa correctamente, un respirador (NIOSH aprobado para vapor orgánico, de serie P pre-filtrado particulado) podría ofrecer protección adicional; obtenga información profesional antes de usar. **PRIMEROS AUXILIOS:** Si tiene dificultad al respirar, alejese y obtenga aire fresco. Si continúan las dificultades obtenga ayuda médica de inmediato. En caso de contacto con los ojos, enjuague rápidamente con suficiente agua por lo menos 15 minutos y obtenga atención médica; para la piel, lave completamente con agua y jabón. Si se ingiere, obtenga atención médica de inmediato. **PRECAUCIÓN: NO SE DEJE AL ALCANCE DE LOS NIÑOS—NO LO INGERIR.**

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-888-683-5667 for product replacement or a full refund of the purchase price. Refer to product number and UPC code on the label.

RUST-OLEUM
CORPORATION
11 Hawthorn Pkwy.
Vernon Hills, IL 60061

rustoleum.com 1-888-683-5667

©2016 Rust-Oleum Corporation
Made in USA 313751 0816

214382 HEAVY DUTY DEGREASER



0 20066 13226 2