

• TRUSTED QUALITY SINCE 1921 •
RUST-OLEUM
HOME®

RUST-OLEUM HOME® CREATIVE ACCENTS

DESCRIPTION AND USES

Rust-Oleum HOME® Creative Accents gives users the ability to add unique design elements, such as a stencil pattern or marbling effect, to their coating project while using any Rust-Oleum HOME Coating System.

Available in two tintable bases that can be matched to any color within the Rust-Oleum HOME Floor Coating palette at the local paint store.

PRODUCT FEATURES

- Works between any Rust-Oleum HOME base coat and top coat system
- Tintable to any Rust-Oleum HOME Floor Coating Color

PRODUCTS

SKU	DESCRIPTION (8 oz.)
391466	HOME Creative Accents White Tint Base
391467	HOME Creative Accents Deep Tint Base

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

IMPORTANT: All surfaces should be tested for adhesion before coating the entire surface. Clean a small 3"x3", inconspicuous area, let dry. Apply HOME Base Coat over area and allow to dry for 12 hours. Take a utility knife and make an X in the coating down to the surface. Apply a 4" piece of duct tape over the X and press firmly. Remove the tape with one quick pull. If more than 10% of the coating comes off, the surface will need to be sanded with 60-80 grit sandpaper before coating the entire surface.

SURFACE PREPARATION

Rinse or sweep away any dirt and dust. Clean the entire surface with a cleaner degreaser, such as Original Krud Kutter® Cleaner Degreaser. Rinse thoroughly and allow to dry completely. For any areas where caulk is present, caulk needs to be removed before applying coating. For waxed surfaces, wax needs to be removed before applying coating. **NOTE:** Failure to follow this preparation method may result in poor adhesion and possible coating failure.

WARNING! If you scrape, sand, or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Rust-Oleum HOME Creative Accents paint is ready to use. Do not thin. Stir thoroughly before use. Apply after Rust-Oleum HOME Base Coat fully dries (sold separately; see product for instructions). If using more than one jar of the same color of Creative Accents, intermix jars together for color uniformity. Apply when air, material, and surface temperatures are between 50-90°F (10-32°C) and relative humidity is below 85%. Use a tack cloth to remove lint and debris before applying over the HOME Base Coat. Lightly apply paint using a brush or 3/8" nap roller. Use rags or paper towels to remove excess paint from brush or roller to prevent stencil bleed. Do not let product puddle. Wait 6 hours before applying necessary touch-ups. Let touched-up areas dry for 1-2 hours (dry to touch) before applying Rust-Oleum HOME Top Coat (sold separately; see product for instructions).

IMPORTANT: Rust-Oleum HOME® Base Coat and Top Coat are required for the project.

DRY & TOPCOAT TIMES

For full system, allow 24 hours for light use. Allow 72 hours before replacing heavy items or furniture (avoid dragging). Full cure is 7 days. Do not wash before 7 days.

CLEAN UP AND STORAGE

Use water and mild detergent. Dried product can be removed with lacquer/thinner. Protect unused product from freezing. Fully cured coated surface may be cleaned with mild soap and water after 7 days. Do not use an abrasive cleaner.

LIMITATIONS

Do not use on exterior spaces or garage floors. Do not use on interior surfaces that are sealed with a superhydrophobic sealer. Not for use inside showers. Not food safe.

MAINTENANCE

Fully cured coated surface may be cleaned with mild soap and water or a general-purpose cleaner such as Original Krud Kutter Cleaner Degreaser after 7 days. Do not use an abrasive cleaner.

	TECHNICAL DATA	ROC-276
<small>• TRUSTED QUALITY SINCE 1921 •</small> RUST-OLEUM HOME®	RUST-OLEUM HOME® CREATIVE ACCENTS	

PHYSICAL PROPERTIES

RUST-OLEUM HOME CREATIVE ACCENTS		
Resin Type/Composition		Water-based Styrene Acrylic
Pigment		Varies with color
Solvent		Water, Propylene Glycol
Weight	Per Gallon	10.1-10.6 lbs.
	Per Liter	1.2-1.3 kg
Solids	By Weight	47.2-51.2%
	By Volume	36.0-37.3%
Volatile Organic Compounds		<50 g/l
Recommended Dry Film Thickness (DFT) Per Coat		1.5-2.0 mils
Wet Film Thickness (WFT) to Achieve DFT		4.0-5.0 mils
Practical Coverage at Recommended DFT		19-25 sq. ft. Coverage will vary depending on surface porosity and texture
Dry Times @ 77°F (25°C) and 50% Relative Humidity	Touch	30-60 minutes
	Recoat/Topcoat	6 hours
	Foot Traffic	6 hours
	Normal Use	NA
	Full Cure	7 days
Flash Point		>200°F (93°C)
Shelf Life		2 years
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 866-765-4474
www.rustoleum.com/rohome

Form: EJ-157
Rev.: 031124