

NO INK OR COATING



IT'S THAT TOUGH!

BEST FOR	Garages, Basements, Workshops, Laundry Rooms, Mud Rooms & More Use in areas with moisture, dirt, grease and other contaminants. Not recommended for damp environments.
SUBSTRATES	Concrete, Previously Coated Surfaces, Wood, Tile See instructions for proper surface preparation.
KIT COVERAGE	Up to 650-800 Sq. Ft. (over coated) / Up to 200-250 Sq. Ft. (over bare)
# GARAGE	2.5 Car (over coated) / 1 Car (over bare)

PROJECT DETAILS QUICK GLANCE

WALK-ON READY	> 8-10 Hours
DRIVE READY	> 1 Day
# COATS NEEDED	> 1 Coat
APPLY WHEN TEMPERATURE IS	> BETWEEN 40°-90° F

FEATURES & BENEFITS

DRIVE ON IN 1 DAY	20X STRONGER THAN EPOXY	1 COAT APPLICATION
NO HOT TIRE PICK UP	EXTREME HIGH GLOSS	WATERPROOFING SEALER
EXCELLENT CHEMICAL RESISTANCE	SELF-LEVELING AND BUILDABLE	LOW ODOR AND LOW VOC*
EASY MIX BURST POUCH		

CLEAR

GARAGE FLOOR COATING

CLEAR

GARAGE FLOOR COATING

CLEAR

GARAGE FLOOR COATING

CLEAR

GARAGE FLOOR COATING

EASY 3-STEP APPLICATION

1 PREPARE SURFACE

- **Coated Surface:** If coating within 7 days of applying a RockSolid Floor Coating, wipe surface clear to remove dust and other contaminants. If applying after 7 days, scuff sand coated surface and clean.

- Rinse thoroughly & allow to dry completely

2 BURST-SHAKE-POUR



- Roll the A side of pouch toward B side to burst and mix the two components
- Mix contents by shaking pouch back and forth and squeezing the edges and corners for 2-3 minutes
- Cut off one corner and pour out a

3 APPLY COATING



Trim outer edges
Apply coating in 4' x 4' sections
with roller
Anti-Skid (included) is recommended
for increased slip-resistance; see
instructions

VISIT RUSTOLEUM.COM/GARAGE FOR INSTRUCTIONAL VIDEOS, FAQs AND TIPS & TECHNIQUES

NO INK OR
COATING

NO INK OR
COATING