



RUST-OLEUM® AUTOMOTIVE LOW VOC EPOXY & LACQUER THINNER

DESCRIPTION AND USES

Rust-Oleum® Low VOC Epoxy & Lacquer Thinner is a blended, low VOC solvent designed for use with most lacquer based wood and metal finishes. Lacquer Thinner is compatible with acrylic, epoxies, automotive or other specialty lacquers. It is suitable for thinning lacquer based paints, epoxies, and clear finishes to improve leveling and reduce viscosity without affecting clarity and gloss. Carefully read all directions, notes and cautions prior to use.

PRODUCTS

SKU	DESCRIPTION
261195	1-Gallon
261196	1-Quart

PRODUCT APPLICATION

INSTRUCTIONS

Use only with adequate ventilation. Always follow the paint manufacturer's instructions for proper reduction ratios. Do not use more than recommended. Protect hands with solvent-resistant gloves and eyes with safety glasses. Add gradually and stir until desired consistency is obtained. Excessive amounts may decrease hiding power or cause blushing. Clean brushes and spray equipment as long as lacquer remains wet on the tools. Do not use to remove large areas of carpet adhesive, asphalt tile or carpet cement. For this use a non-flammable remover. Do not use on rubber, plastic, linoleum or synthetic bristle brushes.

NOTE: Lacquer Thinner is extremely flammable and should not be used for cleaning or degreasing large areas. If you are using this product in the workplace, read the Material Safety Data Sheet before using.

PHYSICAL PROPERTIES

LOW VOC EPOX & LACQUER THINNER		
Solvent Type		Blend of Acetone and Oxsol
Weight	Per Gallon	7.0 lbs.
	Per Liter	0.84 kg
VOC		0 g/l
Shelf Life		5 years
Flash Point		-4°F (-20°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.