

FOR THE BEAUTY OF WOOD



BUTCHER BLOCK OIL + STAIN

ONE STEP PROTECTION & COLOR

Safe for Food Contact

Wood Cutting Boards, Butcher Blocks,
Salad Bowls and More

EBONY

16 fl oz (473ml)

WARNING! COMBUSTIBLE LIQUID AND VAPOR. Read cautions on side/back.
¡ADVERTENCIA! LÍQUIDO Y VAPOR INFLAMABLES. Lea las advertencias en la parte lateral/posterior.



WATCO® BUTCHER BLOCK OIL + STAIN

WATCO® Butcher Block Oil + Stain is specially formulated for use on wooden butcher blocks, cutting boards, salad bowls and other wood applications which require a food safe finish. Easy to apply and maintain, it is nontoxic and safe for food contact when fully dried (meets government standards of 21CFR 175.300). More durable than traditional butcher block oils, WATCO Butcher Block Oil + Stain provides a rich lustrous color and sheen while actually protecting your wood surfaces.

Recommended Uses: Butcher Blocks, Wooden Bowls, Utensils, and Furniture.

PREPARATION: To maintain WATCO Butcher Block Oil + Stain nontoxicity and food safety, apply the finish over raw wood. Prepare the wood for finishing by sanding with #150 and #220 grit sandpaper in the direction of the grain. Before applying oil, remove all grease, glue, or wax and vacuum all sanding dust and dirt.

DIRECTIONS:

1. MIX CONTAINER THOROUGHLY.
2. Apply WATCO Butcher Block Oil with a soft, clean cloth.
3. Allow 6 hours dry time before re-coating.
4. Prior to re-coating, lightly scuff sand with #400 grit sandpaper.
5. Repeat steps 1-4. Allow 72 hours prior to normal use.
6. Hand wash surface prior to contact with food. DO NOT WASH IN DISHWASHER.

APPLICATION TIPS: Apply at room temperature (approx. 72°F). WATCO Butcher Block Oil + Stain is a ready-to-use product. Do not thin. If desired, use additional coats of WATCO Butcher Block Oil + Stain to build a finish. Do not apply over other finishes. When used on objects with small openings, such as canisters, proper drying may be inhibited when applied on interior surfaces.

CLEAN UP: Use mineral spirits.

COVERAGE: Approximately 140 sq. feet per pint.

WARNING! CONTAINS PETROLEUM DISTILLATES AND XYLENE.

VAPOR HARMFUL. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, nose, throat and skin irritation. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN, FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **⚠ WARNING: Cancer – www.P65Warnings.ca.gov.**

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-901-0411 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

DANGER: Rags, steel wool or other waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. **DISPOSAL:** Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

¡ADVERTENCIA! CONTIENE DESTILADOS DE PETRÓLEO Y XILENO. EL VAPOR ES PERJUDICIAL.

Puede afectar el cerebro o el sistema nervioso y causar mareos, náuseas o dolor de cabeza. Causa irritación de los ojos, la nariz, la garganta y la piel. **AVISO:** Algunos informes han asociado la sobreexposición ocupacional repetida y prolongada a solventes con daños permanentes en el cerebro y en el sistema nervioso. El uso inadecuado e intencional al inhalar y concentrar deliberadamente el contenido del producto puede ser perjudicial o mortal. Mantenga lejos del calor y las llamas. Abra todos los ventanales y puertas para lograr una ventilación cruzada y evitar la acumulación de los vapores. **Utilícelo solo con la ventilación adecuada.** No inhale polvo, vapores ni riego. Asegure la entrada de aire fresco durante la aplicación y el secado. Si le lloran los ojos, tiene dolores de cabeza o mareos, o el control del aire demuestra que los niveles de vapor o riego son superiores a los límites aplicables, use un respirador apropiado que se ajuste adecuadamente (aprobado por NIOSH, Instituto Nacional para la Seguridad y Salud Ocupacional) durante y después de la aplicación. Siga las instrucciones de uso del respirador proporcionadas por el fabricante. Evite el contacto con los ojos, la piel y la ropa. Lávese bien después de manipular el producto. **MANTENGA EL PRODUCTO ALEJADO DEL ALCANCE DE LOS NIÑOS. PRIMEROS AUXILIOS:** En caso de contacto con los ojos, enjuague inmediatamente con abundante agua durante por lo menos 15 minutos y busque atención médica de inmediato. En caso de contacto con la piel, lave bien con agua y jabón. Si tiene dificultades para respirar, abandone el área en busca de aire fresco. Si la dificultad persiste, busque atención médica de inmediato. En caso de ingestión, no induzca el vómito. Busque atención médica de inmediato. **⚠ ADVERTENCIA: Cáncer – www.P65Warnings.ca.gov.**

PELIGRO: Los trapos, virutilla o cualquier otro material saturado con este producto puede causar un incendio espontáneo si se desecha en una forma inapropiada. Inmediatamente después del uso, ponga los trapos, virutilla y todos los desechos en un contenedor de metal lleno de agua y cierre bien. **DISPOSICIÓN:** Deseche el absorbente contaminado, contenedor, y el contenido de material no usado de acuerdo a las regulaciones locales, estatales, y federales.

RUST-OLEUM

CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-901-0411 rustoleum.com

Made in USA | Hecho en E.U.A.

©2020 Rust-Oleum Corporation L359023-P 0220

359023 WATCO BUTCHER BLOCK EBONY



FOR THE BEAUTY OF WOOD



BUTCHER BLOCK OIL + STAIN

ONE STEP PROTECTION & COLOR

Safe for Food Contact

Wood Cutting Boards, Butcher Blocks,
Salad Bowls and More

HAZELNUT

16 fl oz (473ml)

WARNING! COMBUSTIBLE LIQUID AND VAPOR. Read cautions on side/back.
¡ADVERTENCIA! LÍQUIDO Y VAPOR INFLAMABLES. Lea las advertencias en la parte lateral/posterior.



WATCO® BUTCHER BLOCK OIL + STAIN

WATCO® Butcher Block Oil + Stain is specially formulated for use on wooden butcher blocks, cutting boards, salad bowls and other wood applications which require a food safe finish. Easy to apply and maintain, it is nontoxic and safe for food contact when fully dried (meets government standards of 21CFR 175.300). More durable than traditional butcher block oils, WATCO Butcher Block Oil + Stain provides a rich lustrous color and sheen while actually protecting your wood surfaces.

Recommended Uses: Butcher Blocks, Wooden Bowls, Utensils, and Furniture.

PREPARATION: To maintain WATCO Butcher Block Oil + Stain nontoxicity and food safety, apply the finish over raw wood. Prepare the wood for finishing by sanding with #150 and #220 grit sandpaper in the direction of the grain. Before applying oil, remove all grease, glue, or wax and vacuum all sanding dust and dirt.

DIRECTIONS:

1. MIX CONTAINER THOROUGHLY.
2. Apply WATCO Butcher Block Oil with a soft, clean cloth.
3. Allow 6 hours dry time before re-coating.
4. Prior to re-coating, lightly scuff sand with #400 grit sandpaper.
5. Repeat steps 1-4. Allow 72 hours prior to normal use.
6. Hand wash surface prior to contact with food. DO NOT WASH IN DISHWASHER.

APPLICATION TIPS: Apply at room temperature (approx. 72°F). WATCO Butcher Block Oil + Stain is a ready-to-use product. Do not thin. If desired, use additional coats of WATCO Butcher Block Oil + Stain to build a finish. Do not apply over other finishes. When used on objects with small openings, such as canisters, proper drying may be inhibited when applied on interior surfaces.

CLEAN UP: Use mineral spirits.

COVERAGE: Approximately 140 sq. feet per pint.

WARNING! CONTAINS PETROLEUM DISTILLATES AND XYLENE.

VAPOR HARMFUL. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, nose, throat and skin irritation. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN, FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **⚠ WARNING: Cancer – www.P65Warnings.ca.gov.**

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-901-0411 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

DANGER: Rags, steel wool or other waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. **DISPOSAL:** Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

¡ADVERTENCIA! CONTIENE DESTILADOS DE PETRÓLEO Y XILENO. EL VAPOR ES PERJUDICIAL.

Puede afectar el cerebro o el sistema nervioso y causar mareos, náuseas o dolor de cabeza. Causa irritación de los ojos, la nariz, la garganta y la piel. **AVISO:** Algunos informes han asociado la sobreexposición ocupacional repetida y prolongada a solventes con daños permanentes en el cerebro y en el sistema nervioso. El uso inadecuado e intencional al inhalar y concentrar deliberadamente el contenido del producto puede ser perjudicial o mortal. Mantenga lejos del calor y las llamas. Abra todos los ventanales y puertas para lograr una ventilación cruzada y evitar la acumulación de los vapores. **Utilícelo solo con la ventilación adecuada.** No inhale polvo, vapores ni riego. Asegure la entrada de aire fresco durante la aplicación y el secado. Si le lloran los ojos, tiene dolores de cabeza o mareos, o el control del aire demuestra que los niveles de vapor o riego son superiores a los límites aplicables, use un respirador apropiado que se ajuste adecuadamente (aprobado por NIOSH, Instituto Nacional para la Seguridad y Salud Ocupacional) durante y después de la aplicación. Siga las instrucciones de uso del respirador proporcionadas por el fabricante. Evite el contacto con los ojos, la piel y la ropa. Lávese bien después de manipular el producto. **MANTENGA EL PRODUCTO ALEJADO DEL ALCANCE DE LOS NIÑOS. PRIMEROS AUXILIOS:** En caso de contacto con los ojos, enjuague inmediatamente con abundante agua durante por lo menos 15 minutos y busque atención médica de inmediato. En caso de contacto con la piel, lave bien con agua y jabón. Si tiene dificultades para respirar, abandone el área en busca de aire fresco. Si la dificultad persiste, busque atención médica de inmediato. En caso de ingestión, no induzca el vómito. Busque atención médica de inmediato. **⚠ ADVERTENCIA: Cáncer – www.P65Warnings.ca.gov.**

SATISFACCION GARANTIZADA: Si no está satisfecho con este producto, comuníquese con el Soporte Técnico de Rust-Oleum al 800-901-0411 para obtener un reembolso del total del precio de compra. Consulte el número de producto y el código de lote.

PELIGRO: Los trapos, virutilla o cualquier otro material saturado con este producto puede causar un incendio espontáneo si se desecha en una forma inapropiada. Inmediatamente después del uso, ponga los trapos, virutilla y todos los desechos en un contenedor de metal lleno de agua y cierre bien. **DISPOSICION:** Deseche el absorbente contaminado, contenedor, y el contenido de material no usado de acuerdo a las regulaciones locales, estatales, y federales.

RUST-OLEUM

CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-901-0411 rustoleum.com

Made in USA | Hecho en E.U.A.

©2020 Rust-Oleum Corporation L359024-P 0220

359024 WATCO BUTCHER BLOCK HAZELNUT

