

• TRUSTED QUALITY SINCE 1921 •  
**RUST-OLEUM®**  
 SPECIALTY

# RUST-OLEUM® TRIPLE THICK GLAZE

## DESCRIPTION AND USES

Rust-Oleum® Triple Thick Glaze is a clear protective coating that gives a glass-like crystal clear finish. It provides a protective, non-yellowing top coat that applies thicker than other clear coatings. Great for wood, metal, wicker, plastic, glass, plaster, ceramic and paper. Can be used on interior and exterior surfaces.

## PRODUCT

SKU	DESCRIPTION (Aerosol)
301416	Triple Thick Glaze

## PRODUCT APPLICATION

### SURFACE PREPARATION

Remove all dirt, grease, oil, salt, and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces.

**WARNING!** If you scrape, sand, or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## PRODUCT APPLICATION (cont.)

### APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 8-10" from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart. **Do not use near open flame.**

### DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 5 minutes and to handle in 20 minutes. Fully dry in 24 hours. Apply clear in 2-3 light coats a few minutes apart.

### CLEAN-UP

Wipe off tip before storing. Clean up wet paint with xylol or mineral spirits. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

### CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

	<b>TECHNICAL DATA</b>	<b>SPC-98</b>
• TRUSTED QUALITY SINCE 1921 • <b>RUST-OLEUM®</b> SPECIALTY	<b>RUST-OLEUM®</b> <b>TRIPLE THICK GLAZE</b>	

## PHYSICAL PROPERTIES

TRIPLE THICK GLAZE		
Resin Type	Acrylic	
Pigment Type	NA	
Solvents	Acetone, Toluene, Ethyl 3-Ethoxypropionate	
MIR	0.85 Max	
Fill Weight	12 ounces	
Wet Film to Achieve DFT	2 wet coats	
Practical Coverage (assumes 15% material loss)	10-12 sq.ft./can. (0.9-1.1 m <sup>2</sup> /can)	
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	5 minutes
	Handle	20 minutes
	Fully Dry	24 Hours
Shelf Life	5 years	
Flash Point	-156°F (-104°C)	
Safety Information	For additional information, see SDS	

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, Illinois 60061

Phone: 800-481-4785  
www.rustoleum.com

Form: ARJ-1784  
Rev.: 100223