



RUST-OLEUM® CUSTOM CLEAR PREMIUM LACQUER PAINT

DESCRIPTION AND USES

Rust-Oleum® Custom Automotive Clear is a premium automotive lacquer designed to add a clear protective finish to your projects. With a fast-drying smooth finish, long-lasting protection and durability, and excellent coverage.

NOTE: Do not use Rust-Oleum Custom Lacquer over existing air-dried enamel paints.

PRODUCT

SKU	DESCRIPTION (Aerosol)
323383	Gloss Clear

PRODUCT APPLICATION

SURFACE PREPARATION

Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry.

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F and 90°F (10-32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after mixing ball begins to rattle. If the mixing ball fails to rattle, DO NOT STRIKE. Contact Rust-Oleum. Shake often during use. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart. Do not use near open flame.

DRY AND RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 1 hour, fully dry in 24 hours. Apply a second coat any time. Apply a clear top coat for maximum durability.

CLEAN UP

When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean up wet paint with xylol or acetone. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as acetone. Do not stick a pin or other objects into the stem.

	TECHNICAL DATA	RCS-03
	RUST-OLEUM® CUSTOM CLEAR PREMIUM LACQUER PAINT	

PHYSICAL PROPERTIES

CLEAR PREMIUM LACQUER PAINT		
Resin Type	Acrylic	
Pigment Type	NA	
Solvents	Ketones, Dimethyl Carbonate	
MIR	0.85 max	
Fill Weight	11 oz.	
Recommended Dry Film Thickness (DFT) Per Coat	1.5–2.5 mils	
Dry times at 77°F (25°C) and 50% Relative Humidity	Touch	20 minutes
	Handle	30 minutes
	Recoat	Anytime
Shelf Life	5 years	
Dry Heat Resistance	200°F	
Flash Point	-156°F	
Safety Information	For Additional Information, See SDS	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.