



**UNIVERSAL®
AGED METALLIC SPRAYS**

DESCRIPTION AND USES

Universal® Aged Metallic Spray is a versatile all-surface paint that provides a durable protective coating with excellent resistance to rust, and excellent resistance to abrasion, fading, chipping, and dulling. Universal Aged Metallic Spray is suitable for use on metal, wood, plastic, wicker and aluminum. This spray applies easily, provides excellent coverage and dries fast to a tough attractive finish. Universal features a comfort grip trigger that reduces fatigue caused by continuous spraying and an any-angle tip which allows you to spray at any angle.

TIP: Some plastics made of polyethylene such as plastic storage containers are manufactured in a way that may hinder maximum paint adhesion. Test paint in a hidden area first.

PRODUCTS

SKU	DESCRIPTION (Aerosol)
285073	Weathered Steel
285072	Aged Metallic Rust
342918	Vintage Gold

PRODUCT APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50-90°F (10-32°C) and humidity is below 65% to ensure proper drying. Do not use on objects that may exceed 200°F (93°C) surface temperature.

Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile.

PRODUCT APPLICATION (cont.)

SURFACE PREPARATION (cont.)

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN**. Contact Rust-Oleum. Shake often during use. Prior to use, slide off the red safety clip from the trigger. Test paint in an inconspicuous area first to ensure desired results.

For best results, lay object horizontally on a flat surface. Hold can upright 12-24" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply one light coat, allow to dry for 3-5 minutes, and follow with one heavier coat at moderate speed, spraying continuously over the object. If needed, recoat after 3-5 minutes. Do not use near open flame.

DRY & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 1 hour, to handle in 2-3 hours, and is fully dry in 48-72 hours. Apply additional coats at any time, but for best results wait 5 minutes between coats.

CLEAN-UP

When finished spraying, wipe off tip before storing. Clean up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.



**UNIVERSAL®
AGED METALLIC SPRAYS**

PHYSICAL PROPERTIES

		UNIVERSAL AGED METALLIC SPRAYS
Resin Type		Alkyd Modified Hydrocarbon
Pigment Type		Aluminum
Solvents		N-Butyl Acetate, VM&P Naphtha, Xylene
MIR		1.25 Max
Fill Weight		11 oz.
Recommended Dry Film Thickness (DFT) per Coat		1.0-2.0 mils (25-50μ)
Practical Coverage at Recommended DFT (assume 15% material loss)		10-15 sq.ft./can (0.9-1.4 m ² /can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	1 hour
	Handle	2 - 3 hours
	Recoat	Recoat anytime, for best results, wait 5 minutes between coats
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-140°F (-96°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.